

Global grade of Antimony Trioxide for flame retardant “PATOX-MK”

PATOX-MK is Antimony Trioxide for general purposes, manufactured by our Chinese partner through production agreement by utilizing our refinery processing technique supported by the long experiences as a leading antimony manufacturer.

This has an equivalent property to the reliable brand of our PATOX-M, and is the grade for wide application as flame retardant.

Specification

		<u>Guaranteed Spec.</u>
Antimony trioxide	Sb ₂ O ₃	99.5 % min.
Arsenic	As	0.1 % max.
Lead	Pb	0.1 % max.
Iron	Fe	0.01 % max.
Sulfur	S	0.01 % max.
Color tone L*		97.0 min.
Average particle size		0.40 – 0.60 μm

Characteristics

PATOX-MK is widely used as a flame retardant of various plastics products for the car, the office automation apparatus, home appliance, and the building material, etc. in the global market including Southeast Asia.



Packing and Origin

25 kgs net in bags

Inner Lining	: 1-ply polyethylene
Outer Lining	: 3-ply kraft paper.
Total	: 4-ply

Country of origin: Made in China

* The statement and methods presented herein about the products are based upon the best available data and practices currently known to us. However they are neither presentations nor warranties of performance, results or comprehensiveness of such data, and further they do not imply any recommendation to infringe any patent or offer of a license under any license.



Head Office	3-2 Shimomiyabi-cho, Shinjuku-ku, Tokyo 162-0822, Japan TEL 81-3-3235-0021 81-3-3235-0031 (Sales Department) FAX 81-3-5261-7335
Osaka Branch	Daido Seimei South Building, 1-2-11 Edobori, Nishi-ku Osaka 550-0002, Japan TEL 81-6-6361-3431 FAX 81-6-6367-8124
Nakase Refinery	1198 Yoshii, Yabu-shi, Hyogo 667-1111, Japan TEL 81-79-667-2121 FAX 81-79-663-5000